

**Product: LUBRAX TOP AUTO 5W20 SQ SINT** 

SDS ID: 1026776 Revision date: 08/08/2025

## **SECTION 1: Identification**

#### 1.1. GHS Product identifier

Product form : Mixture

Trade name : LUBRAX VALORA SQ

Product code : 1026776

Product group : Produtos comerciais

#### 1.2. Other means of identification

No additional information available

### 1.3. Recommended use of the chemical and restrictions on use

Recommended use : Lubricant oil.

1.4. Supplier's details

Name of company : Vibra Energia S.A.

Address : Rua Correia Vasques, 250

Rio de Janeiro

Brasil 20.211-140

SAC : 4090 1337 ou 0800 770 1337 (capitals, metropolitan regions or other

regions)

Emergency telephone number : 0800 024 44 33

1.5. Emergency phone number

Emergency number : 0800 024 44 33 CAE (Emergency Support Center), for leaks, spills and

other accidents that require emergency support.

## SECTION 2: Hazard identification

#### 2.1. Classification of the substance or mixture

Classification according to GHS BR (ABNT NBR 14725: 2023)

Chemical product not classified as hazardous according to ABNT NBR 14725

### 2.2. GHS Label elements, including precautionary statements

**GHS BR labelling** 

Precautionary statements (GHS BR)



**Product: LUBRAX TOP AUTO 5W20 SQ SINT** 

SDS ID: 1026776 Revision date: 08/08/2025

### 2.3. Other hazards which do not result in classification

No additional information available

# SECTION 3: Composition/information on ingredients

#### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	GHS Product identifier	%	Classification according to GHS BR (ABNT NBR 14725: 2023)
Mineral oil	CAS-No.: 64742-54-7, 64742-65-0, 64742-55- 8, e 64742-56-9	2 - 4	Asp. Tox. 1, H304
Distillates (petroleum), hydrotreated light paraffinic	CAS-No.: 64742-55-8	0,5 - 2	Asp. Tox. 1, H304

Comments : The mineral oils present in the product are highly refined and contain

<3% DMSO extract (IP 346).

## SECTION 4: First-aid measures

#### 4.1. Description of necessary first-aid measures

First-aid measures general : If you feel unwell, seek medical advice.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.

First-aid measures after skin contact : After contact with skin, take off immediately all contaminated clothing,

and wash immediately with plenty of water. Be careful, the product may remain trapped under clothing, footwear or a wrist-watch.

First-aid measures after eye contact : In case of contact with eyes, rinse immediately with plenty of water

and seek medical advice.

First-aid measures after ingestion : Do NOT induce vomiting. Rinse mouth out with water.

#### 4.2. Most important symptoms and effects, acute and delayed

Symptoms/effects after inhalation : May cause irritation to the respiratory tract, sneezing, coughing,

burning sensation of throat with constricting sensation of the larynx and

difficulty in breathing.

Symptoms/effects after skin contact : Causes mild skin irritation. Itching.

Symptoms/effects after eye contact : May cause eye irritation.

Symptoms/effects after ingestion : None under normal conditions.



**Product: LUBRAX TOP AUTO 5W20 SQ SINT** 

SDS ID: 1026776 Revision date: 08/08/2025

### 4.3. Indication of any immediate medical attention and special treatment needed, if necessary

Notes to physician : Treat symptomatically

## SECTION 5: Fire-fighting measures

### 5.1. Suitable extinguishing media

Suitable extinguishing media : Water spray. dry chemical powder, foam for use in hydrocarbons,

carbon dioxide (CO2).

Unsuitable extinguishing media : Do not use a heavy water stream.

### 5.2. Specific hazards arising from the chemical

Fire hazard : In case of fire and/or explosion do not breathe fumes.

Explosion hazard : No direct explosion hazard.

### 5.3. Special protective actions for fire-fighters

Firefighting instructions : Fight fire with normal precautions from a reasonable distance. Do not

enter fire area without proper protective equipment, including

respiratory protection.

Protection during firefighting : Use self-contained breathing apparatus and chemically protective

clothing.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Avoid contact with skin and eyes. Stop leak if safe to do so. Notify

authorities if product enters sewers or public waters. Absorb spillage to

prevent material damage.

#### 6.1.1. For non-emergency personnel

Protective equipment : Wear recommended personal protective equipment.

Emergency procedures : Evacuate area. Only qualified personnel equipped with suitable

protective equipment may intervene. Notify fire brigade and

environmental authorities.

## 6.1.2. For emergency responders

Protective equipment : Self-contained breathing apparatus. Equip cleanup crew with proper

protection.

Emergency procedures : Evacuate unnecessary personnel. Stop leak if safe to do so.

### 6.2. Environmental precautions

Avoid release to the environment. Notify authorities if product enters sewers or public waters.



**Product: LUBRAX TOP AUTO 5W20 SQ SINT** 

SDS ID: 1026776 Revision date: 08/08/2025

### 6.3. Methods and materials for containment and cleaning up

For containment : Absorb spilled material with sand or earth. Contain any spills with dikes

or absorbents to prevent migration and entry into sewers or streams.

Stop leak without risks if possible.

Methods for cleaning up : Clean contaminated surfaces with an excess of water.

## SECTION 7: Handling and storage

## 7.1. Precautions for safe handling

Additional hazards when processed : Not expected to present a significant hazard under anticipated

conditions of normal use.

Precautions for safe handling : Keep only in original container. Do not handle until all safety

precautions have been read and understood.

Hygiene measures : Always wash hands after handling the product. Remove contaminated

clothes. Do not eat, drink or smoke when using this product.

## 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Keep in a cool, well-ventilated place away from heat.

Storage conditions : Keep cool. Protect from sunlight.

Packaging materials : Store always product in container of same material as original

container.

# SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

### Exposure limit for mists/aerosols that may form while using this product:

Name	Mineral oil, excluding metal working fluids - pure, highly and severely refined
TWA - (ACGIH, 2024)	5 mg/m <sup>3</sup>

### 8.2. Appropriate engineering controls

Appropriate engineering controls : Emergency eye wash fountains and safety showers should be available

in the immediate vicinity of any potential exposure.

### 8.3. Individual protection measures

### Personal protective equipment:

Wear recommended personal protective equipment.



Product: LUBRAX TOP AUTO 5W20 SQ SINT

SDS ID: 1026776 Revision date: 08/08/2025

Hand protection:

Protective gloves

Eye protection:

Wear security glasses which protect from splashes

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

Where exposure through inhalation may occur from use, respiratory protection equipment is recommended

### Personal protective equipment symbol(s):







# SECTION 9: Physical and chemical properties

#### 9.1. Basic physical and chemical properties

Physical state : Liquid

Appearance : Clear Liquid.

Colour : Brown

Odour : Typical of lubricant oil

Odour threshold : Not available pH : Not available Melting point : Not available Freezing point : Not available Boiling point : Not available Flash point : 222 °C (COC) Relative evaporation rate : Not available

(butylacetate=1)

Flammability : Not available
Explosive limits : Not available
Vapour pressure : Not available
Relative vapour density at 20°C : Not available
Relative density : 0,8469 (20/4°C)
Density : Not available
Solubility : Not available



**Product: LUBRAX TOP AUTO 5W20 SQ SINT** 

SDS ID: 1026776 Revision date: 08/08/2025

: Not available

Partition coefficient n-octanol/water

(Log Kow)

Auto-ignition temperature : Not available Decomposition temperature : Not available

: 44 cSt Kinematic Viscosity (40°C)

Particle size : Not applicable : Not applicable Particle size distribution : Not applicable Particle shape : Not applicable Particle aspect ratio Particle specific surface area : Not applicable

### 9.2. Data relevant with regard to physical hazard classes

No additional information available

#### 9.3. Further safety characteristics

No additional information available

# SECTION 10: Stability and reactivity

Chemical stability : Stable under normal conditions of use.

Conditions to avoid : Extremely high or low temperatures. Keep away from heat, hot

surfaces, sparks, open flames and other ignition sources. No smoking.

Hazardous decomposition products

Incompatible materials

: No hazardous decomposition products known at room temperature. : Consult supplier(s) of these materials for specific recommendations.

Possibility of hazardous reactions

Reactivity

: None under normal use.

: The product is non-reactive under normal conditions of use, storage and

transport.

Handling temperature : No additional information available

# **SECTION 11: Toxicological information**

### 11.1. Information on toxicological effects

Acute toxicity (oral) : Not available Acute toxicity (dermal) : Not available Acute toxicity (inhalation) : Not available

Distillates (petroleum), hydrotreated light paraffinic (64742-55-8)	
LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity), Guideline: OECD Guideline 420 (Acute Oral Toxicity - Fixed Dose Method)
LD50 dermal rabbit	> 2000 mg/kg Source: IUCLID
LC50 Inhalation - Rat (Dust/Mist)	2,18 mg/l Source: IUCLID



**Product: LUBRAX TOP AUTO 5W20 SQ SINT** 

SDS ID: 1026776 Revision date: 08/08/2025

Skin corrosion/irritation : Not available

Serious eye damage/irritation : Not available

Respiratory or skin sensitisation : Not available

Germ cell mutagenicity : Not available

Carcinogenicity : Not available

Reproductive toxicity : Not available STOT-single exposure : Not available

STOT-repeated exposure : Not available

Distillates (petroleum), hydrotreated light paraffinic (64742-55-8)		
LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)	
NOAEC (inhalation, rat, dust/mist/fume, 90 days)	> 0,98 mg/l air Animal: rat, Guideline: OECD Guideline 412 (Subacute Inhalation Toxicity: 28-Day Study)	

Aspiration hazard : Not available

Other information : This mixture does not contain carcinogenic ingredients. The mineral oils

present in the product are highly refined and contain <3% DMSO extract

(IP 346).

LUBRAX TOP AUTO 5W20 SQ SINT	
Kinematic Viscosity (40°C)	44 mm <sup>2</sup> /s

Distillates (petroleum), hydrotreated light paraffinic (64742-55-8)	
Kinematic Viscosity (40°C)	1,99 - 847 mm²/s Temp.: '40°C' Parameter: 'mm²/smm2/s '

## 11.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation : May cause irritation to the respiratory tract, sneezing, coughing,

burning sensation of throat with constricting sensation of the larynx and

difficulty in breathing.

Symptoms/effects after skin contact

: Causes mild skin irritation. Itching.

Symptoms/effects after eye contact

Symptoms/effects after ingestion

: May cause eye irritation.

Symptoms/effects after ingestion : None under normal conditions.



Product: LUBRAX TOP AUTO 5W20 SQ SINT

SDS ID: 1026776 Revision date: 08/08/2025

# **SECTION 12: Ecological information**

### 12.1. Toxicity

Hazardous to the aquatic environment,

: Not classified.

short-term (acute)

Hazardous to the aquatic environment,

: Not classified.

long-term (chronic)

Distillates (petroleum), hydrotreated light paraffinic (64742-55-8)	
LC50 - Fish [1]	> 5000 mg/l Source: IUCLID
LC50 - Other aquatic organisms [1]	> 10 mg/l
EC50 - Crustacea [1]	> 10000 mg/l
NOEC chronic crustacea	= 10 mg/l

### 12.2. Persistence and degradability

LUBRAX TOP AUTO 5W20 SQ SINT	
Persistence and degradability	Rapidly degradable

### 12.3. Bioaccumulative potential

Distillates (petroleum), hydrotreated light paraffinic (64742-55-8)	
Partition coefficient n-octanol/water (Log	3,9 - 6 Source: IUCLID
Pow)	

### 12.4. Mobility in soil

No additional information available

### 12.5. Other adverse effects

Hazardous to the ozone layer : Not available

# **SECTION 13: Disposal considerations**

Regional waste regulation : Law No. 12.305 on the National Policy on Solid Waste Management, 02

August 2010.

: Must follow special treatment according to local regulation.

Sewage disposal recommendations

According to ABNT NBR 14725: 2023

: Disposal must be done according to official regulations.

Product/Packaging disposal

Waste treatment methods

: Disposal must be done according to official regulations.

recommendations

: Do not re-use empty containers.



**Product: LUBRAX TOP AUTO 5W20 SQ SINT** 

SDS ID: 1026776 Revision date: 08/08/2025

# **SECTION 14: Transport information**

In accordance with IMDG / IATA / ANTT

### 14.1 National and international Regulations

### Overland transport

UN-No. (ANTT) : 3082

Proper Shipping Name (ANTT) : Not applicable

Dangerous for the environment : No

### Transport by sea

UN-No. (IMDG) : Not applicable Proper Shipping Name (IMDG) : Not applicable Class (IMDG) : Not applicable Subsidiary hazard (IMDG) : Not applicable : Not applicable Packing group (IMDG) EmS-No. (Fire) : Not applicable EmS-No. (Spillage) : Not applicable Special provisions (IMDG) : Not applicable

### Air transport

UN-No. (IATA) : Not applicable
Proper Shipping Name (IATA) : Not applicable
Class (IATA) : Not applicable
Subsidiary hazards (IATA) : Not applicable
Packing group (IATA) : Not applicable
Special provisions (IATA) : Not applicable

### 14.2 Other informations

No additional information available



**Product: LUBRAX TOP AUTO 5W20 SQ SINT** 

SDS ID: 1026776 Revision date: 08/08/2025

## **SECTION 15: Regulatory information**

## 15.1. National regulations

Brazil Local Regulations

: Norma ABNT NBR 14725.

Federal Decree no. 10.088, of 5 November 2019 - Promulgates Convention no. 170 of the WLO, relating to Safety in the Use of Chemicals in the Workplace, ratified by the Federative Republic of

Brazil.

Ministerial Order no. 2.770, of 5 September 2022 - Approves the new

wording of Regulatory Standard No. 26

Federal Decree no. 96.044, of 18 May 1988 - Approves Regulations for

Road Transportation of Hazardous Materials

Resolution no. 5998, of 03 November 2022, updates the regulation for

road transport of dangerous goods, approves its Complementary

Instructions, and other measures.

## **SECTION 16: Other information**

#### No additional information available

Safety Data Sheet (SDS), Brazil

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.