

Product: Lubrax TOP AUTO 5W40 502/505

SDS ID: 1026778 Revision date: 01/08/2025

SECTION 1: Identification

1.1. GHS Product identifier

Product form : Mixture

Trade name : Lubrax Valora

Product code : 1026778

Product group : Produtos comerciais

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Recommended use : Lubricant oil.

1.4. Supplier's details

Name of company : Vibra Energia S.A.

Address : Rua Correia Vasques, 250

Rio de Janeiro

Brasil 20.211-140

SAC : 4090 1337 ou 0800 770 1337 (capitals, metropolitan regions or other

regions)

Emergency telephone number : 0800 024 44 33

1.5. Emergency phone number

Emergency number : 0800 024 44 33 CAE (Emergency Support Center), for leaks, spills and

other accidents that require emergency support.

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Classification according to GHS BR (ABNT NBR 14725: 2023)

Serious eye damage/eye irritation, Category 2



Product: Lubrax TOP AUTO 5W40 502/505

SDS ID: 1026778 Revision date: 01/08/2025

2.2. GHS Label elements, including precautionary statements

GHS BR labelling

Hazard pictograms (GHS BR)

Signal word (GHS BR) : Warning

Hazard statements (GHS BR) : H319 - Causes serious eye irritation

Precautionary statements (GHS BR)

Prevention : P264 - Wash hands, forearms and face thoroughly after handling.

P280 - Wear protective gloves, protective clothing, eye protection, face

protection and hearing protection.

Response : P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several

minutes. Remove contact lenses, if present and easy to do. Continue

rinsing.

P337+P313 - If eye irritation persists: Get medical advice or attention.

2.3. Other hazards which do not result in classification

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	GHS Product identifier	%	Classification according to GHS BR (ABNT NBR 14725: 2023)
Phosphorodithioic acid, 0,0-di-C1-14-alkyl esters, zinc salts	CAS-No.: 68649-42-3	,	Acute Tox. 5 (Oral), H303 Eye Dam. 1, H318 Aquatic Acute 2, H401 Aquatic Chronic 2, H411

Comments : The mineral oils present in the product are highly refined and contain

<3% DMSO extract (IP 346).

SECTION 4: First-aid measures

4.1. Description of necessary first-aid measures

First-aid measures general : If you feel unwell, seek medical advice.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.



Product: Lubrax TOP AUTO 5W40 502/505

SDS ID: 1026778 Revision date: 01/08/2025

First-aid measures after skin contact : After contact with skin, take off immediately all contaminated clothing,

and wash immediately with plenty of water. Be careful, the product may remain trapped under clothing, footwear or a wrist-watch.

First-aid measures after eye contact : In case of contact with eyes, rinse immediately with plenty of water

and seek medical advice.

First-aid measures after ingestion : Do NOT induce vomiting. Rinse mouth out with water.

4.2. Most important symptoms and effects, acute and delayed

Symptoms/effects : May cause severe burns.

Symptoms/effects after inhalation : May cause irritation to the respiratory tract, sneezing, coughing,

burning sensation of throat with constricting sensation of the larynx and

difficulty in breathing.

Symptoms/effects after skin contact

: Causes skin irritation. irritation (itching, redness, blistering).

Symptoms/effects after eye contact

: May cause eye irritation.

Symptoms/effects after ingestion

: Burns or irritation of the linings of the mouth, throat, and

gastrointestinal tract.

4.3. Indication of any immediate medical attention and special treatment needed, if necessary

Notes to physician : Treat symptomatically

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Suitable extinguishing media : Water spray. dry chemical powder, foam for use in hydrocarbons,

carbon dioxide (CO2).

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Fire hazard : In case of fire and/or explosion do not breathe fumes.

Explosion hazard : No direct explosion hazard.

5.3. Special protective actions for fire-fighters

Firefighting instructions : Fight fire with normal precautions from a reasonable distance. Do not

enter fire area without proper protective equipment, including

respiratory protection.

Protection during firefighting : Use self-contained breathing apparatus and chemically protective

clothing.



Product: Lubrax TOP AUTO 5W40 502/505

SDS ID: 1026778 Revision date: 01/08/2025

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Avoid contact with skin and eyes. Stop leak if safe to do so. Notify

authorities if product enters sewers or public waters. Absorb spillage to

prevent material damage.

6.1.1. For non-emergency personnel

Protective equipment : Wear recommended personal protective equipment.

Emergency procedures : Evacuate area. Only qualified personnel equipped with suitable

protective equipment may intervene. Notify fire brigade and

environmental authorities.

6.1.2. For emergency responders

Protective equipment : Self-contained breathing apparatus. Equip cleanup crew with proper

protection

Emergency procedures : Evacuate unnecessary personnel. Stop leak if safe to do so.

6.2. Environmental precautions

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

6.3. Methods and materials for containment and cleaning up

For containment : Absorb spilled material with sand or earth. Contain any spills with dikes

or absorbents to prevent migration and entry into sewers or streams.

Stop leak without risks if possible.

Methods for cleaning up : Clean contaminated surfaces with an excess of water.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Not expected to present a significant hazard under anticipated

conditions of normal use.

Precautions for safe handling : Keep only in original container. Do not handle until all safety

precautions have been read and understood.

Hygiene measures : Always wash hands after handling the product. Remove contaminated

clothes. Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Keep in a cool, well-ventilated place away from heat.

Storage conditions : Keep cool. Protect from sunlight.



Product: Lubrax TOP AUTO 5W40 502/505

SDS ID: 1026778 Revision date: 01/08/2025

Packaging materials : Store always product in container of same material as original

container.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limit for mists/aerosols that may form while using this product:

Name	Mineral oil, excluding metal working fluids - pure, highly and severely refined
TWA - (ACGIH, 2024)	5 mg/m ³

8.2. Appropriate engineering controls

Appropriate engineering controls : Emergency eye wash fountains and safety showers should be available

in the immediate vicinity of any potential exposure.

8.3. Individual protection measures

Personal protective equipment:

Wear recommended personal protective equipment.

Hand protection:

Protective gloves made of PVC

Eye protection:

Wear security glasses which protect from splashes

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

Where exposure through inhalation may occur from use, respiratory protection equipment is recommended

Personal protective equipment symbol(s):









Product: Lubrax TOP AUTO 5W40 502/505

SDS ID: 1026778 Revision date: 01/08/2025

SECTION 9: Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state : Liquid
Appearance : Clear Liquid.
Colour : light brown

Odour : Typical of lubricant oil

Odour threshold : Not available pH : Not available Melting point : Not available Freezing point : Not available Boiling point : Not available Flash point : 235 °C (COC) Relative evaporation rate : Not available

(butylacetate=1)

Flammability : Not available **Explosive limits** : Not available Vapour pressure : Not available Relative vapour density at 20°C : Not available Relative density $\approx 0.86 (20/4^{\circ}C)$: Not available Density Solubility : Not available Partition coefficient n-octanol/water : Not available

(Log Kow)

Auto-ignition temperature : Not available Decomposition temperature : Not available Kinematic Viscosity (40° C) : $\approx 87 \text{ cSt}$

Particle size : Not applicable
Particle size distribution : Not applicable
Particle shape : Not applicable
Particle aspect ratio : Not applicable
Particle specific surface area : Not applicable

9.2. Data relevant with regard to physical hazard classes

No additional information available

9.3. Further safety characteristics

No additional information available

SECTION 10: Stability and reactivity

Chemical stability : Stable under normal conditions of use.



Product: Lubrax TOP AUTO 5W40 502/505

SDS ID: 1026778 Revision date: 01/08/2025

Conditions to avoid : Extremely high or low temperatures. Keep away from heat, hot

surfaces, sparks, open flames and other ignition sources. No smoking.

Hazardous decomposition products

: No hazardous decomposition products known at room temperature.

Incompatible materials

: Consult supplier(s) of these materials for specific recommendations.

Possibility of hazardous reactions

: None under normal use.

Reactivity

: The product is non-reactive under normal conditions of use, storage and

transport.

Handling temperature : No additional information available

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not available
Acute toxicity (dermal) : Not available
Acute toxicity (inhalation) : Not available

Phosphorodithioic acid, 0,0-di-C1-14-alkyl esters, zinc salts (68649-42-3)		
LD50 oral rat	2230 - 3100 mg/kg	
LD50 dermal rat	> 2000 mg/kg	
LD50 dermal rabbit	> 3160 mg/kg Source: ECHA	
LC50 Inhalation - Rat	> 5 mg/l air Animal: rat, Guideline: other:	
ATE BR (oral)	2230 mg/kg bodyweight	

Skin corrosion/irritation : Not available

Phosphorodithioic acid, 0,0-di-C1-14-alkyl esters, zinc salts (68649-42-3)	
pH	5,5 - 7,5 Concentration: 1 vol%

Serious eye damage/irritation : Causes serious eye irritation.

Phosphorodithioic acid, 0,0-di-C1-14-alkyl esters, zinc salts (68649-42-3)	
Н	5,5 - 7,5 Concentration: 1 vol%

Respiratory or skin sensitisation : Not available

Germ cell mutagenicity : Not available

Carcinogenicity : Not available

Phosphorodithioic acid, 0,0-di-C1-14-alkyl esters, zinc salts (68649-42-3)	
NOAEL (animal/female, F0/P)	300 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: other:



Product: Lubrax TOP AUTO 5W40 502/505

SDS ID: 1026778 Revision date: 01/08/2025

Phosphorodithioic acid, 0,0-di-C1-14-alkyl esters, zinc salts (68649-42-3)

NOAEL (animal/female, F1) 1000 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline:

other:

Reproductive toxicity : Not available STOT-single exposure : Not available

STOT-repeated exposure : Not available

Aspiration hazard : Not available

Other information : This mixture does not contain carcinogenic ingredients. The mineral oils

present in the product are highly refined and contain <3% DMSO extract

(IP 346).

Lubrax TOP AUTO 5W40 502/505

Kinematic Viscosity (40°C) ≈ 87 mm²/s

Phosphorodithioic acid, 0,0-di-C1-14-alkyl esters, zinc salts (68649-42-3)

Kinematic Viscosity (40°C) 9 - 15 mm²/s Temp.: 'other:' Parameter: 'kinematic viscosity (in

mm²/s)'

11.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : May cause severe burns.

Symptoms/effects after inhalation : May cause irritation to the respiratory tract, sneezing, coughing,

burning sensation of throat with constricting sensation of the larynx and

difficulty in breathing.

Symptoms/effects after skin contact

: Causes skin irritation. irritation (itching, redness, blistering).

Symptoms/effects after eye contact

: May cause eye irritation.

Symptoms/effects after ingestion : Burns

: Burns or irritation of the linings of the mouth, throat, and

gastrointestinal tract.

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, : Not classified.

short-term (acute)

Hazardous to the aquatic environment, : Not classified.

long-term (chronic)



Product: Lubrax TOP AUTO 5W40 502/505

SDS ID: 1026778 Revision date: 01/08/2025

Phosphorodithioic acid, 0,0-di-C1-14-alkyl esters, zinc salts (68649-42-3)	
EC50 - Crustacea [1]	1 - 1,5 mg/l Source: IUCLID
EC50 96h - Algae [1]	1 - 5 mg/l Source: IUCLID

12.2. Persistence and degradability

Lubrax TOP AUTO 5W40 502/505	
Persistence and degradability	Rapidly degradable

12.3. Bioaccumulative potential

Phosphorodithioic acid, 0,0-di-C1-14-alkyl esters, zinc salts (68649-42-3)	
Partition coefficient n-octanol/water (Log	14,876 Source: ECHA
Pow)	

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Hazardous to the ozone layer : Not available

SECTION 13: Disposal considerations

Regional waste regulation : Law No. 12.305 on the National Policy on Solid Waste Management, 02

August 2010.

Waste treatment methods : Must follow special treatment according to local regulation.

Sewage disposal recommendations : Disposal must be done according to official regulations.

Product/Packaging disposal : Disposal must be done according to official regulations.

recommendations

Additional information : Do not re-use empty containers.

SECTION 14: Transport information

In accordance with IMDG / IATA / ANTT

14.1 National and international Regulations

Overland transport

UN-No. (ANTT) : Not applicable
Proper Shipping Name (ANTT) : Not applicable
Class (ANTT) : Not applicable
Subsidiary risk (ANTT) : Not applicable
Risk Number (ANTT) : Not applicable
Packing group (ANTT) : Not applicable



Product: Lubrax TOP AUTO 5W40 502/505

SDS ID: 1026778 Revision date: 01/08/2025

Special provisions (ANTT) : Not applicable

Transport by sea

UN-No. (IMDG) : Not applicable Proper Shipping Name (IMDG) : Not applicable Class (IMDG) : Not applicable Subsidiary hazard (IMDG) : Not applicable Packing group (IMDG) : Not applicable EmS-No. (Fire) : Not applicable EmS-No. (Spillage) : Not applicable Special provisions (IMDG) : Not applicable

Air transport

UN-No. (IATA) : Not applicable
Proper Shipping Name (IATA) : Not applicable
Class (IATA) : Not applicable
Subsidiary hazards (IATA) : Not applicable
Packing group (IATA) : Not applicable
Special provisions (IATA) : Not applicable

14.2 Other informations

No additional information available

SECTION 15: Regulatory information

15.1. National regulations

Brazil Local Regulations : Norma ABNT NBR 14725.

Federal Decree no. 10.088, of 5 November 2019 - Promulgates Convention no. 170 of the WLO, relating to Safety in the Use of Chemicals in the Workplace, ratified by the Federative Republic of

Brazil.

Ministerial Order no. 2.770, of 5 September 2022 - Approves the new

wording of Regulatory Standard No. 26

Federal Decree no. 96.044, of 18 May 1988 - Approves Regulations for

Road Transportation of Hazardous Materials

Resolution no. 5998, of 03 November 2022, updates the regulation for road transport of dangerous goods, approves its Complementary

Instructions, and other measures.

SECTION 16: Other information

No additional information available

Safety Data Sheet (SDS), Brazil



Product: Lubrax TOP AUTO 5W40 502/505

SDS ID: 1026778 Revision date: 01/08/2025

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.