

SDS ID: 1014945

Revision date: 24/08/2023

SECTION 1: Identification of Product and Company

: LUBRAX AV 70 IN
: 1014945
: Insulating dieletric mineral oil
: Vibra Energia S.A.
: Rua Correia Vasques, 250
Rio de Janeiro
Brasil
20.211-140
: 4090 1337 (capitais ou regiões metropolitanas) ou 0800 770 1337 (demais regiões)
 0800 024 44 33 - CAE (Central de apoio a emergências), para vazamentos, derramamentos e outros acidentes que necessitem de suporte emergencial.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to GHS BR (ABNT NBR 14725)

Aspiration hazard, Category 1

2.2. Label elements

GHS BR labelling

Hazard pictograms (GHS BR)

Signal word (GHS BR) Hazard statements (GHS BR) Precautionary statements (GHS BR) Resposta a Emergência



: Danger

:

: H304 - May be fatal if swallowed and enters airways.

: P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor.

P331 - Do NOT induce vomiting.

: P405 - Store locked up.

Storage



SDS ID: 1014945

Revision date: 24/08/2023

Disposição

: P501 - Dispose of contents and container in accordance with local regulations.

2.3. Other hazards not contributing to the classification

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to GHS BR (ABNT NBR 14725)
Distillates (petroleum), hydrotreated light naphthenic	CAS-No.: 64742-53-6	≥ 90	Asp. Tox. 1, H304
2,6-di-terc-Butil-p-cresol	CAS-No.: 128-37-0	0,3	Aquatic Acute 1, H400

Comments

: The mineral oils present in the product are highly refined and contain <3% DMSO extract (IP 346).

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general First-aid measures after inhalation	 If you feel unwell, seek medical advice. If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. 	
First-aid measures after skin contact	: After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water.	
First-aid measures after eye contact	: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.	
First-aid measures after ingestion	: Do not induce vomiting/risk of damage to lungs exceeds poisoning risk.	
4.2. Most important symptoms and effects, both acute and delayed		

Symptoms/effects	: May be fatal if swallowed and enters airways.
Symptoms/effects after inhalation	: Although no appropriate human or animal health effects data are known
	to exist, this material is expected to be an inhalation hazard.
Symptoms/effects after skin contact	: None under normal conditions.



SDS ID: 1014945

Revision date: 24/08/2023

Symptoms/effects after eye contact	: None under normal conditions.
Symptoms/effects after ingestion	: Risk of lung oedema.

4.3. Indication of any immediate medical attention and special treatment needed

Notes to physician	: Treat symptomatically
--------------------	-------------------------

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Water spray. dry chemical powder, foam for use in hydrocarbons, carbon dioxide (CO2).
Unsuitable extinguishing media	: Do not use a heavy water stream.
5.2. Special hazards arising from t	he substance or mixture
Fire hazard	: No fire hazard.
Explosion hazard	: No direct explosion hazard.
5.3. Advice for firefighters	
Firefighting instructions	: Fight fire with normal precautions from a reasonable distance. Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting	: Wear recommended personal protective equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material damage.
6.1.1. For non-emergency personnel	
Protective equipment	: Wear recommended personal protective equipment.
Emergency procedures	: Evacuate area. Only qualified personnel equipped with suitable protective equipment may intervene. Notify fire brigade and environmental authorities.
6.1.2. For emergency responders	
Protective equipment	: Equip cleanup crew with proper protection.
Emergency procedures	: Evacuate unnecessary personnel. Stop leak if safe to do so.



SDS ID: 1014945

Revision date: 24/08/2023

6.2. Environmental precautions

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment	: Absorb spilled material with sand or earth. Contain any spills with dikes
	or absorbents to prevent migration and entry into sewers or streams.
	Stop leak without risks if possible.
Methods for cleaning up	: Take up liquid spill into absorbent material.

SECTION 7: Handling and storage

7.1. Precautions for safe handling	
Additional hazards when processed	: Not expected to present a significant hazard under anticipated conditions of normal use.
Precautions for safe handling	: Do not get in eyes, on skin, or on clothing. Keep only in original container. Do not handle until all safety precautions have been read and understood.
Hygiene measures	: Do not eat, drink or smoke when using this product.
7.2. Conditions for safe storage, incl	uding any incompatibilities
Technical measures	 Store locked up

Technical measures	: Store locked up.
Storage conditions	: Keep cool. Protect from sunlight.
Packaging materials	: Store always product in container of same material as original
	container.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

2,6-di-terc-Butil-p-cresol (128-37-0)	
USA - ACGIH - Occupational Exposure Limits	
Remark (ACGIH)	URT irr

Exposure limit for mists/aerosols that may form while using this product:

Name	Mineral oil, excluding working fluids - poorly and mildy refined
TWA - (ACGIH, 2023)	5 ppm



SDS ID: 1014945 Revision date: 24/08/2023 8.2. Exposure controls Appropriate engineering controls : Ensure good ventilation of the work station. 8.3. Personal protective equipment Personal protective equipment: Wear recommended personal protective equipment. Hand protection: Protective gloves Eye protection: Wear security glasses which protect from splashes

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

No respiratory protection needed under normal use conditions

Personal protective equipment symbol(s):



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Clear Liquid.
Colour	: Colourless
Odour	: characteristic
Odour threshold	: Not available
рН	: Not available
Melting point	: Not available
Freezing point	: Not available



SDS ID: 1014945

Boiling point : Not available Flash point : 146 °C (COC) : Not available Relative evaporation rate (butylacetate=1) Flammability : Not available **Explosive** limits : Not available Vapour pressure : Not available Relative vapour density at 20°C : Not available **Relative density** : 0,88 (20/4°C) Solubility : Not available Partition coefficient n-octanol/water : Not available (Log Kow) : Not available Auto-ignition temperature Decomposition temperature : Not available Kinematic Viscosity (40°C) : 10 cSt Viscosity, dynamic : Not available

Revision date: 24/08/2023

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity Chemical stability : Stable under normal conditions of use. Conditions to avoid : Extremely high or low temperatures. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

: No additional information available

Hazardous decomposition products Incompatible materials Possibility of hazardous reactions Reactivity Stable under normal conditions of use.
Extremely high or low temperatures. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
No hazardous decomposition products known at room temperature.
Consult supplier(s) of these materials for specific recommendations.
None under normal use.
The product is non-reactive under normal conditions of use, storage and transport.

Handling temperature

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not available
Acute toxicity (dermal)	: Not available



SDS ID: 1014945

Revision date: 24/08/2023

Acute toxicity (inhalation)	:	Not available
Distillates (petroleum), hydrotreated	ligh	t naphthenic (64742-53-6)
LD50 oral rat		> 5000 mg/kg
LD50 dermal rabbit		> 2000 mg/kg
LC50 Inhalation - Rat		= 2,18 mg/l
Skin corrosion/irritation	:	Not available
Serious eye damage/irritation	:	Not available
Respiratory or skin sensitisation	:	Not available
Germ cell mutagenicity	:	Not available
Carcinogenicity	:	Not available
Reproductive toxicity		Not available
STOT-single exposure	:	Not available
STOT-repeated exposure	:	Not available

Distillates (petroleum), hydrotreated light naphthenic (64742-53-6)	
LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
NOAEL (dermal, rat/rabbit, 90 days)	 ≈ 1000 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)
Aspiration hazard	: May be fatal if swallowed and enters airways.
Other information	: This mixture does not contain carcinogenic ingredients. The mineral oils present in the product are highly refined and contain <3% DMSO extract (IP 346).

LUBRAX AV 70 IN	
Kinematic Viscosity (40°C)	10 mm²/s

Distillates (petroleum), hydrotreated light naphthenic (64742-53-6)	
Kinematic Viscosity (40°C)	1,99 - 847 mm ² /s Temp.: '40°C' Parameter: 'mm ² /smm2/s '

11.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects

: May be fatal if swallowed and enters airways.



SDS ID: 1014945

Revision date: 24/08/2023

Symptoms/effects after inhalation	: Although no appropriate human or animal health effects data are known
	to exist, this material is expected to be an inhalation hazard.
Symptoms/effects after skin contact	: None under normal conditions.
Symptoms/effects after eye contact	: None under normal conditions.
Symptoms/effects after ingestion	: Risk of lung oedema.

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, : short-term (acute) Hazardous to the aquatic environment, : long-term (chronic)	Not available Not available	
2,6-di-terc-Butil-p-cresol (128-37-0)		
EC50 - Crustacea [1]	0,48 mg/l	
NOEC (chronic)	0,069 mg/l	
Distillates (petroleum), hydrotreated light naphthenic (64742-53-6)		
LC50 - Fish [1]	> 100 mg/l	
EC50 - Crustacea [1]	> 10000 mg/l	
EC50 72h - Algae [1]	> 100 mg/l	
NOEC chronic crustacea	= 10 mg/l	

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Hazardous to the ozone layer : Not available



SDS ID: 1014945

Revision date: 24/08/2023

SECTION 13: Disposal considerations

Regional legislation (waste)	: Law No. 12.305 on the National Policy on Solid Waste Management, 02 August 2010.
Waste treatment methods Sewage disposal recommendations	: Must follow special treatment according to local regulation. : Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	: Disposal must be done according to official regulations.
Additional information	: Do not re-use empty containers.

SECTION 14: Transport information

14.1 National and international Regulations

Not classified as dangerous for transport in the different modes, but may be harmful in the event of an accident. For further information, please consult Section 2 in this MSDS.

14.2 Other information

No additional information available

SECTION 15: Regulatory information

15.1. National regulations

Brazil Local Regulations :	Norma ABNT NBR 14725.
	Decreto Federal nº 2.657, de 3 de julho de 1998 - Promulga a
	Convenção nº 170 da OIT, relativa à Segurança na Utilização de
	Produtos Químicos no Trabalho, assinada em Genebra, em 25 de junho
	de 1990.
	Portaria nº 229, de 24 de maio de 2011 - Altera a Norma
	Regulamentadora nº 27
	Federal Decree no. 96.044, of 18 May 1988 - Approves Regulations for
	Road Transportation of Hazardous Materials
	Resolution no. 5998, of 03 November 2022, updates the regulation for
	road transport of dangerous goods, approves its Complementary
	Instructions, and other measures.

SECTION 16: Other information

No additional information available

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.