

**Product: LUBRAX FLUIDO PARA RADIADORES HD-2 DILUIDO**

SDS ID: 1015630

Revision date: 25/08/2023

**SECTION 1: Identification of Product and Company****1.1. Product identifier**

Product name : LUBRAX FLUIDO PARA RADIADORES HD-2 DILUIDO  
Product code : 1015630  
Recommended use : Heavy-duty diesel engine cooling system

**1.2. Company identification**

Name of company : Vibra Energia S.A.  
Address : Rua Correia Vasques, 250  
Rio de Janeiro  
Brasil  
20.211-140

SAC : 4090 1337 (capitais ou regiões metropolitanas) ou 0800 770 1337  
(demais regiões)

Emergency telephone number : 0800 024 44 33 - CAE (Central de apoio a emergências), para vazamentos, derramamentos e outros acidentes que necessitem de suporte emergencial.

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Classification according to GHS BR (ABNT NBR 14725)**

Acute toxicity (oral), Category 4

Reproductive toxicity, Category 1B

Specific target organ toxicity - Repeated exposure, Category 1

**2.2. Label elements****GHS BR labelling**

Hazard pictograms (GHS BR)



Signal word (GHS BR)

: Danger

Hazard statements (GHS BR)

: H302 - Harmful if swallowed.

H360 - May damage fertility or the unborn child.

H372 - Causes damage to organs through prolonged or repeated exposure.

Precautionary statements (GHS BR)

**Product: LUBRAX FLUIDO PARA RADIADORES HD-2 DILUIDO**

**SDS ID: 1015630**

**Revision date: 25/08/2023**

Prevention	: P201 - Obtain special instructions before use. P202 - Do not handle until all safety precautions have been read and understood. P260 - Do not breathe mist and vapours. P264 - Wash the exposed areas thoroughly after handling. P270 - Do not eat, drink or smoke when using this product. P280 - Wear protective gloves, protective clothing and eye protection.
Resposta a Emergência	: P301+P312 - IF SWALLOWED: Call a POISON CENTER or doctor if you feel unwell. P308+P313 - IF exposed or concerned: Get medical advice/attention. P314 - Get medical advice/attention if you feel unwell. P330 - Rinse mouth.
Storage	: P405 - Store locked up.
Disposição	: P501 - Dispose of contents and container in accordance with local regulations.

## 2.3. Other hazards not contributing to the classification

No additional information available

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	Classification according to GHS BR (ABNT NBR 14725)
Ethane-1,2-diol	CAS-No.: 107-21-1	< 50	Acute Tox. 4 (Oral), H302 STOT RE 2, H373 Asp. Tox. 2, H305
2,2'-oxydiethanol	CAS-No.: 111-46-6	< 1	Acute Tox. 4 (Oral), H302 STOT RE 2, H373
4-tert-butylbenzoic acid	CAS-No.: 98-73-7	< 2	Acute Tox. 4 (Oral), H302 Repr. 1B, H360 STOT RE 1, H372 Aquatic Chronic 2, H411
Denatonium benzoate	CAS-No.: 3734-33-6	< 1	Acute Tox. 4 (Oral), H302

Product: LUBRAX FLUIDO PARA RADIADORES HD-2 DILUIDO

SDS ID: 1015630

Revision date: 25/08/2023

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general	: IF exposed or concerned: Get medical advice/attention.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water.
First-aid measures after eye contact	: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
First-aid measures after ingestion	: If swallowed, seek medical advice immediately and show this container or label.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: Causes damage to organs through prolonged or repeated exposure. Swallowing a small quantity of this material presents some health hazard.
Symptoms/effects after inhalation	: Although no appropriate human or animal health effects data are known to exist, this material is expected to be an inhalation hazard.
Symptoms/effects after skin contact	: None under normal conditions.
Symptoms/effects after eye contact	: None under normal conditions.
Symptoms/effects after ingestion	: Harmful if swallowed. Ingestion may cause nausea and vomiting.
Chronic symptoms	: May damage fertility. May damage the unborn child.

### 4.3. Indication of any immediate medical attention and special treatment needed

Notes to physician	: Treat symptomatically
--------------------	-------------------------

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media	: Water spray. dry chemical powder, foam for use in hydrocarbons, carbon dioxide (CO <sub>2</sub> ).
Unsuitable extinguishing media	: Do not use a heavy water stream.

### 5.2. Special hazards arising from the substance or mixture

Fire hazard	: In case of fire and/or explosion do not breathe fumes.
Explosion hazard	: No direct explosion hazard.

**Product: LUBRAX FLUIDO PARA RADIADORES HD-2 DILUIDO**

**SDS ID: 1015630**

**Revision date: 25/08/2023**

### 5.3. Advice for firefighters

- |                                |  |
|--------------------------------|--|
| Firefighting instructions      | : Fight fire with normal precautions from a reasonable distance. Do not enter fire area without proper protective equipment, including respiratory protection. |
| Protection during firefighting | : Use self-contained breathing apparatus and chemically protective clothing.   |

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

- |                  |   |
|------------------|---|
| General measures | : Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material damage. |
|------------------|---|

#### 6.1.1. For non-emergency personnel

- |                      |   |
|----------------------|---|
| Protective equipment | : Wear recommended personal protective equipment.   |
| Emergency procedures | : Evacuate area. Only qualified personnel equipped with suitable protective equipment may intervene. Notify fire brigade and environmental authorities. |

#### 6.1.2. For emergency responders

- |                      |   |
|----------------------|---|
| Protective equipment | : Equip cleanup crew with proper protection.                  |
| Emergency procedures | : Evacuate unnecessary personnel. Stop leak if safe to do so. |

### 6.2. Environmental precautions

Do not allow to enter drains or water courses. Notify authorities if product enters sewers or public waters.

### 6.3. Methods and material for containment and cleaning up

- |                         |   |
|-------------------------|---|
| For containment         | : Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak without risks if possible. |
| Methods for cleaning up | : Absorb spilled material with sand or earth. Clean contaminated surfaces with an excess of water. Absorb spillage to prevent material damage.  |

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

- |                                   |  |
|-----------------------------------|--|
| Additional hazards when processed | : Not expected to present a significant hazard under anticipated conditions of normal use. |
|-----------------------------------|--|

**Product: LUBRAX FLUIDO PARA RADIADORES HD-2 DILUIDO****SDS ID: 1015630****Revision date: 25/08/2023**

- Precautions for safe handling : Obtain special instructions before use. Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Limit quantities of product at the minimum necessary for handling and limit the number of exposed workers. Wear personal protective equipment. Do not eat, drink or smoke when using this product. Keep only in original container. Do not handle until all safety precautions have been read and understood.
- Hygiene measures : Always wash hands after handling the product. Remove contaminated clothes. Do not eat, drink or smoke when using this product.

**7.2. Conditions for safe storage, including any incompatibilities**

- Technical measures : Store locked up.
- Storage conditions : Keep cool. Protect from sunlight.
- Packaging materials : Store always product in container of same material as original container.

**SECTION 8: Exposure controls/personal protection****8.1. Control parameters**

Ethane-1,2-diol (107-21-1)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Etileno Glicol - CAS# 107-21-1
ACGIH OEL TWA	100 mg/m <sup>3</sup>
ACGIH OEL TWA [ppm]	25 ppm (V - Vapor fraction)
ACGIH OEL STEL	10 mg/m <sup>3</sup>
ACGIH OEL STEL [ppm]	50 ppm
Remark (ACGIH)	URT irr; A4
Regulatory reference	(samente aerossol)

**Exposure limit for mists/aerosols that may form while using this product:****8.2. Exposure controls**

- Appropriate engineering controls : Ensure good ventilation of the work station.

**Product: LUBRAX FLUIDO PARA RADIADORES HD-2 DILUIDO**

SDS ID: 1015630

Revision date: 25/08/2023

## 8.3. Personal protective equipment

**Personal protective equipment:**

Wear recommended personal protective equipment.

**Hand protection:**

Protective gloves

**Eye protection:**

Wear security glasses which protect from splashes

**Skin and body protection:**

Wear suitable protective clothing

**Respiratory protection:**

Where exposure through inhalation may occur from use, respiratory protection equipment is recommended

**Personal protective equipment symbol(s):**



## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Liquid.
Colour	: red
Odour	: Light
Odour threshold	: Not available
pH	: 8,7
Melting point	: Not available
Freezing point	: $\leq -15$ °C
Boiling point	: $\geq 110$ °C
Flash point	: Not available

**Product: LUBRAX FLUIDO PARA RADIADORES HD-2 DILUIDO****SDS ID: 1015630****Revision date: 25/08/2023**

Relative evaporation rate (butylacetate=1)	: Not available
Flammability	: Not available
Explosive limits	: Not available
Vapour pressure	: < 0,1 mm Hg
Relative vapour density at 20 °C	: Not available
Relative density	: 1,07 (20/4 °C)
Density	: 1,07 kg/l
Solubility	: Water:
Partition coefficient n-octanol/water (Log Kow)	: Not available
Auto-ignition temperature	: 398 °C
Decomposition temperature	: Not available
Kinematic Viscosity (40 °C)	: Not available
Viscosity, dynamic	: Not available

**9.2. Other information**

VOC content	: 0 %
-------------	-------

**SECTION 10: Stability and reactivity**

Chemical stability	: Stable under normal conditions of use.
Conditions to avoid	: Extremely high or low temperatures. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Hazardous decomposition products	: No hazardous decomposition products known at room temperature.
Incompatible materials	: Strong acids. Strong bases. Oxidizing agent.
Possibility of hazardous reactions	: None under normal use.
Reactivity	: The product is non-reactive under normal conditions of use, storage and transport.
Handling temperature	: No additional information available

**SECTION 11: Toxicological information****11.1. Information on toxicological effects**

Acute toxicity (oral)	: Harmful if swallowed.
Acute toxicity (dermal)	: Not available
Acute toxicity (inhalation)	: Not available

**Product: LUBRAX FLUIDO PARA RADIADORES HD-2 DILUIDO**

SDS ID: 1015630

Revision date: 25/08/2023

LUBRAX FLUIDO PARA RADIADORES HD-2 DILUIDO	
ATE BR (oral)	980,392 mg/kg bodyweight
Ethane-1,2-diol (107-21-1)	
LD50 oral rat	4000 mg/kg
LD50 dermal rat	9530 µl/kg
ATE BR (oral)	500 mg/kg bodyweight
ATE BR (dermal)	9530 mg/kg bodyweight
2,2'-oxydiethanol (111-46-6)	
LD50 dermal rabbit	11890 mg/kg
ATE BR (oral)	500 mg/kg bodyweight
ATE BR (dermal)	11890 mg/kg bodyweight
Denatonium benzoate (3734-33-6)	
LD50 oral rat	584 mg/kg
ATE BR (oral)	584 mg/kg bodyweight
4-tert-butylbenzoic acid (98-73-7)	
ATE BR (oral)	500 mg/kg bodyweight

Skin corrosion/irritation : Not available  
pH: 8,7

Serious eye damage/irritation : Not available  
pH: 8,7

Respiratory or skin sensitisation : Not available

Germ cell mutagenicity : Not available

Carcinogenicity : Not available

Ethane-1,2-diol (107-21-1)	
NOAEL (chronic, oral, animal/male, 2 years)	1500 mg/kg bodyweight Animal: mouse, Animal sex: male, Remarks on results: other:Effect type: carcinogenicity (migrated information)

Reproductive toxicity : May damage fertility or the unborn child.

STOT-single exposure : Not available

STOT-repeated exposure : Causes damage to organs through prolonged or repeated exposure.

**Product: LUBRAX FLUIDO PARA RADIADORES HD-2 DILUIDO**

SDS ID: 1015630

Revision date: 25/08/2023

Ethane-1,2-diol (107-21-1)	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.

2,2'-oxydiethanol (111-46-6)	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.

4-tert-butylbenzoic acid (98-73-7)	
STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard : Not available

Ethane-1,2-diol (107-21-1)	
Kinematic Viscosity (40 °C)	14,505 mm <sup>2</sup> /s

**11.2. Most important symptoms and effects, both acute and delayed**

Symptoms/effects	: Causes damage to organs through prolonged or repeated exposure. Swallowing a small quantity of this material presents some health hazard.
Symptoms/effects after inhalation	: Although no appropriate human or animal health effects data are known to exist, this material is expected to be an inhalation hazard.
Symptoms/effects after skin contact	: None under normal conditions.
Symptoms/effects after eye contact	: None under normal conditions.
Symptoms/effects after ingestion	: Harmful if swallowed. Ingestion may cause nausea and vomiting.
Chronic symptoms	: May damage fertility. May damage the unborn child.

**SECTION 12: Ecological information****12.1. Toxicity**

Hazardous to the aquatic environment, short-term (acute)	: Not available
Hazardous to the aquatic environment, long-term (chronic)	: Not available

Ethane-1,2-diol (107-21-1)	
LC50 - Fish [1]	72860 mg/l Test organisms (species): Pimephales promelas
EC50 - Crustacea [1]	> 100 mg/l Test organisms (species): Daphnia magna
EC50 96h - Algae [1]	3536 mg/l Test organisms (species): other:greenn algae

**Product: LUBRAX FLUIDO PARA RADIADORES HD-2 DILUIDO**

SDS ID: 1015630

Revision date: 25/08/2023

Ethane-1,2-diol (107-21-1)	
EC50 96h - Algae [2]	6500 - 13000 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
NOEC (chronic)	≥ 1000 mg/l Test organisms (species): Americamysis bahia (previous name: Mysidopsis bahia) Duration: '23 d'
2,2'-oxydiethanol (111-46-6)	
LC50 - Fish [1]	> 500000 ppm

**12.2. Persistence and degradability**

No additional information available

**12.3. Bioaccumulative potential**

No additional information available

**12.4. Mobility in soil**

No additional information available

**12.5. Other adverse effects**

Hazardous to the ozone layer : Not available

**SECTION 13: Disposal considerations**

Regional legislation (waste)	: Law No. 12.305 on the National Policy on Solid Waste Management, 02 August 2010.
Waste treatment methods	: Must follow special treatment according to local regulation.
Sewage disposal recommendations	: Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	: Disposal must be done according to official regulations.
Additional information	: Do not re-use empty containers.

**SECTION 14: Transport information****14.1 National and international Regulations****Overland transport**

UN-No. (ANTT) : 3082

**Product: LUBRAX FLUIDO PARA RADIADORES HD-2 DILUIDO**

**SDS ID: 1015630**

**Revision date: 25/08/2023**

Packing group (ANTT) : II  
Dangerous for the environment : No

#### 14.2 Other information

No additional information available

### SECTION 15: Regulatory information

#### 15.1. National regulations

Brazil Local Regulations : Norma ABNT NBR 14725.  
Decreto Federal nº 2.657, de 3 de julho de 1998 - Promulga a Convenção nº 170 da OIT, relativa à Segurança na Utilização de Produtos Químicos no Trabalho, assinada em Genebra, em 25 de junho de 1990.  
Portaria nº 229, de 24 de maio de 2011 - Altera a Norma Regulamentadora nº 27  
Federal Decree no. 96.044, of 18 May 1988 - Approves Regulations for Road Transportation of Hazardous Materials  
Resolution no. 5998, of November 3, 2022, updates the regulation for road transport of dangerous goods, approves its Complementary Instructions, and other measures.

### SECTION 16: Other information

No additional information available

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.