

Product: LUBRAX GAS 40 MA

SDS ID: 1000324 Revision date: 24/07/2023

# **SECTION 1: Identification of Product and Company**

1.1. Product identifier

Product name : LUBRAX GAS 40 MA

Product code : 1000324
Recommended use : Lubricant oil.

1.2. Company identification

Name of company : Vibra Energia S.A.

Address : Rua Correia Vasques, 250

Rio de Janeiro

Brasil 20.211-140

SAC : 4090 1337 (capitais ou regiões metropolitanas) ou 0800 770 1337

(demais regiões)

**Emergency telephone number** : 0800 024 44 33 - CAE (Central de apoio a emergências), para

vazamentos, derramamentos e outros acidentes que necessitem de

suporte emergencial.

## **SECTION 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

Classification according to GHS BR (ABNT NBR 14725)

Chemical product not classified as hazardous according to Regulation (EC) No. 1272/2008 [CLP]

### 2.2. Label elements

**GHS BR labelling** 

Precautionary statements (GHS BR)

### 2.3. Other hazards not contributing to the classification

No additional information available

# SECTION 3: Composition/information on ingredients

#### 3.1. Substances

Not applicable



**Product: LUBRAX GAS 40 MA** 

SDS ID: 1000324 Revision date: 24/07/2023

### 3.2. Mixtures

Name	Product identifier	%	Classification according to GHS BR (ABNT NBR 14725)
Alkyl phenate sulfide-derived calcium chain	CAS-No.: Confidencial	1 - 5	Aquatic Chronic 4, H413
degraded alkylphenol ester	CAS-No.: Confidencial	0,5 - 2	Aquatic Chronic 4, H413
Alkaryl sulphonate, metal salts	CAS-No.: Confidencial	0,1 - 1	Skin Sens. 1B, H317
Phenol, dodecyl-, branched	CAS-No.: 74499-35-7	< 0,5	Skin Corr. 1C, H314 Repr. 1B, H360 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Branched alkylphenol and branched calcium alkylphenol	CAS-No.: 74499-35-7 & 132752-19-3	< 0,5	Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Repr. 1B, H360 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Ethane-1,2-diol	CAS-No.: 107-21-1	< 0,1	Acute Tox. 4 (Oral), H302 STOT RE 2, H373 Asp. Tox. 2, H305

Comments : The mineral oils present in the product are highly refined and contain

<3% DMSO extract (IP 346).

# **SECTION 4: First aid measures**

### 4.1. Description of first aid measures

First-aid measures general : If you feel unwell, seek medical advice.

First-aid measures after inhalation : If breathing is difficult, remove victim to fresh air and keep at rest in a

position comfortable for breathing. Call a POISON CENTER/doctor if you

feel unwell.

First-aid measures after skin contact : After contact with skin, take off immediately all contaminated clothing,

and wash immediately with plenty of water.

First-aid measures after eye contact : In case of contact with eyes, rinse immediately with plenty of water

and seek medical advice.

First-aid measures after ingestion : Do NOT induce vomiting. Rinse mouth out with water.



Product: LUBRAX GAS 40 MA

SDS ID: 1000324 Revision date: 24/07/2023

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation : Although no appropriate human or animal health effects data are known

to exist, this material is expected to be an inhalation hazard.

Symptoms/effects after skin contact : None under normal conditions. Symptoms/effects after eye contact : None under normal conditions. Symptoms/effects after ingestion : None under normal conditions.

### 4.3. Indication of any immediate medical attention and special treatment needed

Notes to physician : Treat symptomatically

# **SECTION 5: Firefighting measures**

### 5.1. Extinguishing media

Suitable extinguishing media : Water spray. dry chemical powder, foam for use in hydrocarbons,

carbon dioxide (CO2).

Unsuitable extinguishing media : Do not use a heavy water stream.

### 5.2. Special hazards arising from the substance or mixture

Fire hazard : No fire hazard.

Explosion hazard : No direct explosion hazard.

### 5.3. Advice for firefighters

Firefighting instructions : Fight fire with normal precautions from a reasonable distance. Do not

enter fire area without proper protective equipment, including

respiratory protection.

Protection during firefighting : Wear recommended personal protective equipment.

# SECTION 6: Accidental release measures

## 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Stop leak if safe to do so. Notify authorities if product enters sewers or

public waters. Absorb spillage to prevent material damage.

### 6.1.1. For non-emergency personnel

Protective equipment : Wear recommended personal protective equipment.

Emergency procedures : Evacuate area. Only qualified personnel equipped with suitable

protective equipment may intervene. Notify fire brigade and

environmental authorities.



Product: LUBRAX GAS 40 MA

SDS ID: 1000324 Revision date: 24/07/2023

### 6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

Emergency procedures : Evacuate unnecessary personnel. Stop leak if safe to do so.

#### 6.2. Environmental precautions

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

### 6.3. Methods and material for containment and cleaning up

For containment : Absorb spilled material with sand or earth. Contain any spills with dikes

or absorbents to prevent migration and entry into sewers or streams.

Stop leak without risks if possible.

Methods for cleaning up : Take up liquid spill into absorbent material.

# SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Additional hazards when processed : Not expected to present a significant hazard under anticipated

conditions of normal use.

Precautions for safe handling : Keep only in original container. Do not handle until all safety

precautions have been read and understood.

Hygiene measures : Do not eat, drink or smoke when using this product.

#### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Keep in a cool, well-ventilated place away from heat.

Storage conditions : Keep cool. Protect from sunlight.

Packaging materials : Store always product in container of same material as original

container.

# SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

Ethane-1,2-diol (107-21-1)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Etileno Glicol - CAS# 107-21-1
ACGIH OEL TWA	100 mg/m <sup>3</sup>
ACGIH OEL TWA [ppm]	25 ppm (V - Vapor fraction)



**Product: LUBRAX GAS 40 MA** 

SDS ID: 1000324 Revision date: 24/07/2023

Ethane-1,2-diol (107-21-1)	
ACGIH OEL STEL	10 mg/m <sup>3</sup>
ACGIH OEL STEL [ppm]	50 ppm
Remark (ACGIH)	URT irr; A4
Regulatory reference	(somente aerossol)

### Exposure limit for mists/aerosols that may form while using this product:

Name	Mineral oil, excluding working fluids - poorly and mildy refined
TWA - (ACGIH, 2023)	5 ppm

### 8.2. Exposure controls

Appropriate engineering controls : Ensure good ventilation of the work station.

### 8.3. Personal protective equipment

### Personal protective equipment:

Wear recommended personal protective equipment.

Hand	prote	ction:

Protective gloves

### Eye protection:

Wear security glasses which protect from splashes

### Skin and body protection:

Wear suitable protective clothing

## Respiratory protection:

No respiratory protection needed under normal use conditions

### Personal protective equipment symbol(s):









Product: LUBRAX GAS 40 MA

SDS ID: 1000324 Revision date: 24/07/2023

# **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

Physical state : Liquid

Appearance : Clear and Bright Liquid.
Colour : Yellowish to brown

Odour : Typical of lubricant oil

Odour threshold : Not available pH : Not available Melting point : Not available Freezing point : Not available Boiling point : Not available Flash point : 256 °C (COC) Relative evaporation rate : Not available

(butylacetate=1)

Flammability : Not available
Explosive limits : Not available
Vapour pressure : Not available
Relative vapour density at 20°C : Not available
Relative density : 0,8906 (20/4°C)
Solubility : Not available
Partition coefficient n-octanol/water : Not available

(Log Kow)

Auto-ignition temperature : Not available

Decomposition temperature : Not available

Kinematic Viscosity (40°C) : 126,1 cSt

Viscosity, dynamic : Not available

#### 9.2. Other information

No additional information available

# **SECTION 10: Stability and reactivity**

Chemical stability : Stable under normal conditions of use.



Product: LUBRAX GAS 40 MA

SDS ID: 1000324 Revision date: 24/07/2023

Conditions to avoid : Extremely high or low temperatures. Keep away from heat, hot

surfaces, sparks, open flames and other ignition sources. No smoking.

Hazardous decomposition products

: No hazardous decomposition products known at room temperature.

Incompatible materials

: Consult supplier(s) of these materials for specific recommendations.

Possibility of hazardous reactions

: None under normal use.

Reactivity

: The product is non-reactive under normal conditions of use, storage and

transport.

Handling temperature : No additional information available

# **SECTION 11: Toxicological information**

### 11.1. Information on toxicological effects

Acute toxicity (oral) : Not available
Acute toxicity (dermal) : Not available
Acute toxicity (inhalation) : Not available

Phenol, dodecyl-, branched (74499-35-7)	
LD50 dermal rabbit	> 2000 mg/kg
Ethane-1,2-diol (107-21-1)	
LD50 oral rat	4000 mg/kg
LD50 dermal rat	9530 µl/kg
ATE BR (oral)	500 mg/kg bodyweight
ATE BR (dermal)	9530 mg/kg bodyweight

Skin corrosion/irritation : Not available
Serious eye damage/irritation : Not available

Respiratory or skin sensitisation : Not available

Germ cell mutagenicity : Not available

Carcinogenicity : Not available

Ethane-1,2-diol (107-21-1)	
NOAEL (chronic, oral, animal/male, 2	1500 mg/kg bodyweight Animal: mouse, Animal sex: male, Remarks on
years)	results: other:Effect type: carcinogenicity (migrated information)

Reproductive toxicity : Not available STOT-single exposure : Not available

STOT-repeated exposure : Not available



Product: LUBRAX GAS 40 MA

SDS ID: 1000324 Revision date: 24/07/2023

Ethane-1,2-diol (107-21-1)	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard : Not available

Other information : This mixture does not contain carcinogenic ingredients. The mineral oils

present in the product are highly refined and contain <3% DMSO extract

(IP 346).

LUBRAX GAS 40 MA	
Kinematic Viscosity (40°C)	126,1 mm <sup>2</sup> /s

Ethane-1,2-diol (107-21-1)	
Kinematic Viscosity (40°C)	14,505 mm <sup>2</sup> /s

#### 11.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation : Although no appropriate human or animal health effects data are known

to exist, this material is expected to be an inhalation hazard.

Symptoms/effects after skin contact : None under normal conditions. Symptoms/effects after eye contact : None under normal conditions. Symptoms/effects after ingestion : None under normal conditions.

# SECTION 12: Ecological information

## 12.1. Toxicity

Hazardous to the aquatic environment, : Not available

short-term (acute)

Hazardous to the aquatic environment, : Not available

long-term (chronic)

Ethane-1,2-diol (107-21-1)	
LC50 - Fish [1]	72860 mg/l Test organisms (species): Pimephales promelas
EC50 - Crustacea [1]	> 100 mg/l Test organisms (species): Daphnia magna
EC50 96h - Algae [1]	3536 mg/l Test organisms (species): other:grenn algae
EC50 96h - Algae [2]	6500 - 13000 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
NOEC (chronic)	≥ 1000 mg/l Test organisms (species): Americamysis bahia (previous name: Mysidopsis bahia) Duration: '23 d'



Product: LUBRAX GAS 40 MA

SDS ID: 1000324 Revision date: 24/07/2023

### 12.2. Persistence and degradability

No additional information available

### 12.3. Bioaccumulative potential

No additional information available

#### 12.4. Mobility in soil

No additional information available

#### 12.5. Other adverse effects

: Not available Hazardous to the ozone layer

# **SECTION 13: Disposal considerations**

Regional legislation (waste) : Law No. 12.305 on the National Policy on Solid Waste Management, 02

August 2010.

Waste treatment methods : Must follow special treatment according to local regulation.

Sewage disposal recommendations

: Disposal must be done according to official regulations. Product/Packaging disposal : Disposal must be done according to official regulations.

recommendations

Additional information : Do not re-use empty containers.

# **SECTION 14: Transport information**

### 14.1 National and international Regulations

Not classified as dangerous for transport in the different modes, but may be harmful in the event of an accident. For further information, please consult Section 2 in this MSDS.

#### 14.2 Other information

No additional information available



**Product: LUBRAX GAS 40 MA** 

SDS ID: 1000324 Revision date: 24/07/2023

# **SECTION 15: Regulatory information**

### 15.1. National regulations

Brazil Local Regulations : Norma ABNT NBR 14725.

Decreto Federal nº 2.657, de 3 de julho de 1998 - Promulga a Convenção nº 170 da OIT, relativa à Segurança na Utilização de

Produtos Químicos no Trabalho, assinada em Genebra, em 25 de junho

de 1990.

Portaria nº 229, de 24 de maio de 2011 - Altera a Norma

Regulamentadora nº 27

Federal Decree no. 96.044, of 18 May 1988 - Approves Regulations for

Road Transportation of Hazardous Materials

Resolution no. 5998, of 03 November 2022, updates the regulation for

road transport of dangerous goods, approves its Complementary

Instructions, and other measures.

# **SECTION 16: Other information**

#### No additional information available

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.