

Product: LUBRAX RAIL MV 240

SDS ID: 1000782

Revision date: 03/02/2023

SECTION 1: Identification of Product and Company**1.1. Product identifier**

Product name : LUBRAX RAIL MV 240
Product code : 1000782
Recommended use : Lubricant oil.

1.2. Company identification

Name of company : Vibra Energia S.A.
Address : Rua Correia Vasques, 250
Rio de Janeiro
Brasil
20.211-140

SAC : 4090 1337 (capitais ou regiões metropolitanas) ou 0800 770 1337 (demais regiões)

Emergency telephone number : 0800 024 44 33 - CAE (Central de apoio a emergências), para vazamentos, derramamentos e outros acidentes que necessitem de suporte emergencial.

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture**

Classification according to GHS BR (ABNT NBR 14725)

Chemical product not classified as hazardous according to Regulation (EC) No. 1272/2008 [CLP]

2.2. Label elements

GHS BR labelling

Precautionary statements (GHS BR)

2.3. Other hazards not contributing to the classification

No additional information available

SECTION 3: Composition/information on ingredients**3.1. Substances**

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to GHS BR (ABNT NBR 14725)
Lubricant base oil	-	50 - 60	Not classified

Product: LUBRAX RAIL MV 240**SDS ID: 1000782****Revision date: 03/02/2023**

Name	Product identifier	%	Classification according to GHS BR (ABNT NBR 14725)
Lubricant base oil	-	40 - 50	Not classified
Antifoam agent	-	< 0,1	Flam. Liq. 4, H227 Asp. Tox. 1, H304

Comments : The mineral oils present in the product are highly refined and contain <3% DMSO extract (IP 346).

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : If you feel unwell, seek medical advice.

First-aid measures after inhalation : If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.

First-aid measures after skin contact : After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water.

First-aid measures after eye contact : In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

First-aid measures after ingestion : Do NOT induce vomiting. Rinse mouth out with water.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation : Although no appropriate human or animal health effects data are known to exist, this material is expected to be an inhalation hazard.

Symptoms/effects after skin contact : None under normal conditions.

Symptoms/effects after eye contact : None under normal conditions.

Symptoms/effects after ingestion : None under normal conditions.

4.3. Indication of any immediate medical attention and special treatment needed

Notes to physician : Treat symptomatically

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray, dry chemical powder, foam for use in hydrocarbons, carbon dioxide (CO₂).

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard : No fire hazard.

Explosion hazard : No direct explosion hazard.

Product: LUBRAX RAIL MV 240**SDS ID: 1000782****Revision date: 03/02/2023****5.3. Advice for firefighters**

- Firefighting instructions : Fight fire with normal precautions from a reasonable distance. Do not enter fire area without proper protective equipment, including respiratory protection.
- Protection during firefighting : Wear recommended personal protective equipment.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

- General measures : Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material damage.

6.1.1. For non-emergency personnel

- Protective equipment : Wear recommended personal protective equipment.
- Emergency procedures : Evacuate area. Only qualified personnel equipped with suitable protective equipment may intervene. Notify fire brigade and environmental authorities.

6.1.2. For emergency responders

- Protective equipment : Equip cleanup crew with proper protection.
- Emergency procedures : Evacuate unnecessary personnel. Stop leak if safe to do so.

6.2. Environmental precautions

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

- For containment : Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak without risks if possible.
- Methods for cleaning up : Take up liquid spill into absorbent material.

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

- Additional hazards when processed : Not expected to present a significant hazard under anticipated conditions of normal use.
- Precautions for safe handling : Keep only in original container. Do not handle until all safety precautions have been read and understood.
- Hygiene measures : Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Keep in a cool, well-ventilated place away from heat.
- Storage conditions : Keep cool. Protect from sunlight.

Product: LUBRAX RAIL MV 240**SDS ID: 1000782****Revision date: 03/02/2023**

Packaging materials : Store always product in container of same material as original container.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Exposure limit for mists/aerosols that may form while using this product:**

Name	Mineral oil, excluding working fluids - poorly and mildly refined
TWA - (ACGIH, 2021)	5 ppm

8.2. Exposure controls

Appropriate engineering controls : Ensure good ventilation of the work station.

8.3. Personal protective equipment**Personal protective equipment:**

Wear recommended personal protective equipment.

Hand protection:

Protective gloves

Eye protection:

Wear security glasses which protect from splashes

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

No respiratory protection needed under normal use conditions

Personal protective equipment symbol(s):

Product: LUBRAX RAIL MV 240

SDS ID: 1000782

Revision date: 03/02/2023

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state	: Liquid
Appearance	: Clear and Bright Liquid.
Colour	: Yellowish to brown
Odour	: Typical of lubricant oil
Odour threshold	: Not available
pH	: Not available
Melting point	: Not available
Freezing point	: Not available
Boiling point	: Not available
Flash point	: 282 °C (COC)
Relative evaporation rate (butylacetate=1)	: Not available
Flammability	: Not available
Explosive limits	: Not available
Vapour pressure	: Not available
Relative vapour density at 20 °C	: Not available
Relative density	: 0,89 (20/4 °C)
Solubility	: Not available
Partition coefficient n-octanol/water (Log Kow)	: Not available
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
Kinematic Viscosity (40 °C)	: 235 cSt
Viscosity, dynamic	: Not available

9.2. Other information

Not available

SECTION 10: Stability and reactivity

Chemical stability : Stable under normal conditions of use.

Product: LUBRAX RAIL MV 240

SDS ID: 1000782

Revision date: 03/02/2023

Conditions to avoid	: Extremely high or low temperatures. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Hazardous decomposition products	: No hazardous decomposition products known at room temperature.
Incompatible materials	: Consult supplier(s) of these materials for specific recommendations.
Possibility of hazardous reactions	: None under normal use.
Reactivity	: The product is non-reactive under normal conditions of use, storage and transport.
Handling temperature	: No additional information available

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not available
Acute toxicity (dermal)	: Not available
Acute toxicity (inhalation)	: Not available

Lubricant base oil	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 5000 mg/kg

Skin corrosion/irritation	: Not available
Serious eye damage/irritation	: Not available
Respiratory or skin sensitisation	: Not available
Germ cell mutagenicity	: Not available
Carcinogenicity	: Not available
Reproductive toxicity	: Not available
STOT-single exposure	: Not available
STOT-repeated exposure	: Not available
Aspiration hazard	: Not available
Other information	: This mixture does not contain carcinogenic ingredients. The mineral oils present in the product are highly refined and contain <3% DMSO extract (IP 346).

LUBRAX RAIL MV 240	
Kinematic Viscosity (40 °C)	235 mm ² /s

11.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation	: Although no appropriate human or animal health effects data are known to exist, this material is expected to be an inhalation hazard.
Symptoms/effects after skin contact	: None under normal conditions.
Symptoms/effects after eye contact	: None under normal conditions.
Symptoms/effects after ingestion	: None under normal conditions.

Product: LUBRAX RAIL MV 240**SDS ID: 1000782****Revision date: 03/02/2023****SECTION 12: Ecological information****12.1. Toxicity**

Hazardous to the aquatic environment, short-term (acute) : Not available

Hazardous to the aquatic environment, long-term (chronic) : Not available

Lubricant base oil

LC50 - Other aquatic organisms [1]	> 1000 mg/l
------------------------------------	-------------

EC50 - Crustacea [1]	> 1000 mg/l
----------------------	-------------

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

Regional legislation (waste) : Law No. 12.305 on the National Policy on Solid Waste Management, 02 August 2010.

Waste treatment methods : Must follow special treatment according to local regulation.

Sewage disposal recommendations : Disposal must be done according to official regulations.

Product/Packaging disposal recommendations : Disposal must be done according to official regulations.

Additional information : Do not re-use empty containers.

SECTION 14: Transport information**14.1 National and international Regulations**

Not classified as dangerous for transport in the different modes, but may be harmful in the event of an accident.
For further information, please consult Section 2 in this MSDS.

Product: LUBRAX RAIL MV 240

SDS ID: 1000782

Revision date: 03/02/2023

14.2 Other information

No additional information available

SECTION 15: Regulatory information

15.1. National regulations

Brazil Local Regulations

: Norma ABNT NBR 14725.

Decreto Federal nº 2.657, de 3 de julho de 1998 - Promulga a Convenção nº 170 da OIT, relativa à Segurança na Utilização de Produtos Químicos no Trabalho, assinada em Genebra, em 25 de junho de 1990.

Portaria nº 229, de 24 de maio de 2011 - Altera a Norma Regulamentadora nº 27

Federal Decree no. 96.044, of 18 May 1988 - Approves Regulations for Road Transportation of Hazardous Materials

Resolution no. 5947, of 01 June 2021, updates the regulation for road transport of dangerous goods and approves its complementary instructions, and other measures.

SECTION 16: Other information

No additional information available

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.