

Product: LUBRAX TRM 50

SDS ID: 1016653 Revision date: 03/02/2023

SECTION 1: Identification of Product and Company

1.1. Product identifier

Product name : LUBRAX TRM 50

Product code : 1016653

Recommended use : Lubricant oil.

1.2. Company identification

Name of company : Vibra Energia S.A.

Address : Rua Correia Vasques, 250

Rio de Janeiro

Brasil 20.211-140

SAC : 4090 1337 (capitais ou regiões metropolitanas) ou 0800 770 1337

(demais regiões)

Emergency telephone number: 0800 024 44 33 - CAE (Central de apoio a emergências), para

vazamentos, derramamentos e outros acidentes que necessitem de

suporte emergencial.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to GHS BR (ABNT NBR 14725)

Chemical product not classified as hazardous according to Regulation (EC) No. 1272/2008 [CLP]

2.2. Label elements

GHS BR labelling

Precautionary statements (GHS BR)

2.3. Other hazards not contributing to the classification

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier		Classification according to GHS BR (ABNT NBR 14725)
Lubricant base oil	-	50 - 60	Not classified



Product: LUBRAX TRM 50

SDS ID: 1016653 Revision date: 03/02/2023

Name	Product identifier	%	Classification according to GHS BR (ABNT NBR 14725)
Lubricant base oil	-	40 - 50	Not classified
Phosphorodithioic acid, mixed 0,0-bis(sec-Bu and isooctyl) esters, zinc salts	CAS-No.: 113706-15-3	0,1 - 1	Acute Tox. 5 (Oral), H303 Acute Tox. 5 (Dermal), H313 Skin Irrit. 2, H315 Eye Dam. 1, H318 Aquatic Acute 2, H401 Aquatic Chronic 2, H411
Distillates (petroleum), solvent-dewaxed heavy paraffinic	CAS-No.: 64742-65-0	0,1 - 1	Asp. Tox. 1, H304
Viscometric modifier agent	-	0,1 - 1	Not classified
Fumaric acid	CAS-No.: 110-17-8	< 1	Not classified
Ethylenediamine	CAS-No.: 107-15-3	< 0,1	Flam. Liq. 3, H226 Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Dermal), H311 Skin Corr. 1B, H314 Resp. Sens. 1, H334 Skin Sens. 1, H317 Aquatic Acute 3, H402 Aquatic Chronic 3, H412
Antifoam agent	-	< 0,1	Flam. Liq. 4, H227 Asp. Tox. 1, H304

Comments : The mineral oils present in the product are highly refined and contain

<3% DMSO extract (IP 346).

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : If you feel unwell, seek medical advice.

First-aid measures after inhalation : If breathing is difficult, remove victim to fresh air and keep at rest in a

position comfortable for breathing. Call a POISON CENTER/doctor if you

feel unwell.

First-aid measures after skin contact : After contact with skin, take off immediately all contaminated clothing,

and wash immediately with plenty of water.

First-aid measures after eye contact : In case of contact with eyes, rinse immediately with plenty of water

and seek medical advice.

First-aid measures after ingestion : Do NOT induce vomiting. Rinse mouth out with water.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation : Although no appropriate human or animal health effects data are known

to exist, this material is expected to be an inhalation hazard.



Product: LUBRAX TRM 50

SDS ID: 1016653 Revision date: 03/02/2023

Symptoms/effects after skin contactSymptoms/effects after eye contactSymptoms/effects after ingestionNone under normal conditions.None under normal conditions.

4.3. Indication of any immediate medical attention and special treatment needed

Notes to physician : Treat symptomatically

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. dry chemical powder, foam for use in hydrocarbons,

carbon dioxide (CO2).

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard : No fire hazard.

Explosion hazard : No direct explosion hazard.

5.3. Advice for firefighters

Firefighting instructions : Fight fire with normal precautions from a reasonable distance. Do not

enter fire area without proper protective equipment, including

respiratory protection.

Protection during firefighting : Wear recommended personal protective equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Stop leak if safe to do so. Notify authorities if product enters sewers or

public waters. Absorb spillage to prevent material damage.

6.1.1. For non-emergency personnel

Protective equipment : Wear recommended personal protective equipment.

Emergency procedures : Evacuate area. Only qualified personnel equipped with suitable

protective equipment may intervene. Notify fire brigade and

environmental authorities.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

Emergency procedures : Evacuate unnecessary personnel. Stop leak if safe to do so.

6.2. Environmental precautions

Avoid release to the environment. Notify authorities if product enters sewers or public waters.



Product: LUBRAX TRM 50

SDS ID: 1016653 Revision date: 03/02/2023

6.3. Methods and material for containment and cleaning up

For containment : Absorb spilled material with sand or earth. Contain any spills with dikes

or absorbents to prevent migration and entry into sewers or streams.

Stop leak without risks if possible.

Methods for cleaning up : Take up liquid spill into absorbent material.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Not expected to present a significant hazard under anticipated

conditions of normal use.

Precautions for safe handling : Keep only in original container. Do not handle until all safety

precautions have been read and understood.

Hygiene measures : Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Keep in a cool, well-ventilated place away from heat.

Storage conditions : Keep cool. Protect from sunlight.

Packaging materials : Store always product in container of same material as original

container.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Ethylenediamine (107-15-3)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Ethylenediamine
ACGIH OEL TWA [ppm]	10 ppm
Regulatory reference	ACGIH 2018
USA - OSHA - Occupational Exposure Limits	
Local name	Ethylenediamine
OSHA PEL TWA [1]	25 mg/m³
OSHA PEL TWA [2]	10 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1

Exposure limit for mists/aerosols that may form while using this product:

Name	Mineral oil, excluding working fluids - poorly and mildy refined
TWA - (ACGIH, 2021)	5 ppm



Product: LUBRAX TRM 50

SDS ID: 1016653 Revision date: 03/02/2023

8.2. Exposure controls

Appropriate engineering controls : Ensure good ventilation of the work station.

8.3. Personal protective equipment

Personal protective equipment:

Wear recommended personal protective equipment.

Hand protection:

Protective gloves

Eye protection:

Wear security glasses which protect from splashes

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

No respiratory protection needed under normal use conditions

Personal protective equipment symbol(s):







SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid

Appearance : Clear Liquid.
Colour : light brown

Odour : Typical of lubricant oil

Odour threshold : Not available

pH : Not available

Melting point : Not available



Product: LUBRAX TRM 50

SDS ID: 1016653 Revision date: 03/02/2023

: Not available Freezing point **Boiling point** : Not available Flash point : 264 °C (COC)

Relative evaporation rate

(butylacetate=1)

: Not available

Flammability : Not available **Explosive limits** : Not available Vapour pressure : Not available Relative vapour density at 20°C : Not available Relative density $:0,9(20/4^{\circ}C)$

Solubility : Not available

Partition coefficient n-octanol/water

(Log Kow)

: Not available

Auto-ignition temperature : Not available : Not available Decomposition temperature

: 220 cSt Kinematic Viscosity (40°C)

Viscosity, dynamic : Not available

9.2. Other information

Not available

SECTION 10: Stability and reactivity

Chemical stability : Stable under normal conditions of use.

Conditions to avoid : Extremely high or low temperatures. Keep away from heat, hot

surfaces, sparks, open flames and other ignition sources. No smoking.

: No hazardous decomposition products known at room temperature.

Incompatible materials : Consult supplier(s) of these materials for specific recommendations.

Possibility of hazardous reactions : None under normal use.

: The product is non-reactive under normal conditions of use, storage and Reactivity

transport.

Handling temperature : No additional information available

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not available Acute toxicity (dermal) : Not available

Hazardous decomposition products



Product: LUBRAX TRM 50

SDS ID: 1016653 Revision date: 03/02/2023

Acute toxicity (inhalation) : Not available

(
Lubricant base oil		
LD50 oral rat	> 5000 mg/kg	
LD50 dermal rabbit	> 5000 mg/kg	
Phosphorodithioic acid, mixed O,O-bis(sec-Bu and isooctyl) esters, zinc salts (113706-15-3)		
LD50 oral rat	= 2600 mg/kg	
LD50 dermal rabbit	> 3160 mg/kg	
LC50 Inhalation - Rat	> 2 mg/l	
ATE BR (oral)	2500 mg/kg bodyweight	
ATE BR (dermal)	2500 mg/kg bodyweight	
Distillates (petroleum), solvent-dev	waxed heavy paraffinic (64742-65-0)	
LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity), Guideline: OECD Guideline 420 (Acute Oral Toxicity - Fixed Dose Method)	
Ethylenediamine (107-15-3)		
LD50 oral rat	= 866 mg/kg	
LD50 dermal rabbit	= 560 mg/kg	
LC50 Inhalation - Rat	= 14,7 mg/l	
ATE BR (oral)	500 mg/kg bodyweight	
ATE BR (dermal)	300 mg/kg bodyweight	
Skin corrosion/irritation	: Not available	
Serious eye damage/irritation	: Not available	
Respiratory or skin sensitisation	: Not available	
Germ cell mutagenicity	: Not available	
Carcinogenicity	: Not available	
Reproductive toxicity	: Not available	
STOT-single exposure	: Not available	

Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)	
LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
NOAEL (dermal, rat/rabbit, 90 days)	≈ 1000 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)

: Not available

Aspiration hazard : Not available

STOT-repeated exposure



Product: LUBRAX TRM 50

SDS ID: 1016653 Revision date: 03/02/2023

Other information : This mixture does not contain carcinogenic ingredients. The mineral oils

present in the product are highly refined and contain <3% DMSO extract

(IP 346).

LUBRAX TRM 50

Kinematic Viscosity (40°C) 220 mm²/s

11.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation : Although no appropriate human or animal health effects data are known

to exist, this material is expected to be an inhalation hazard.

Symptoms/effects after skin contact : None under normal conditions. Symptoms/effects after eye contact : None under normal conditions. Symptoms/effects after ingestion : None under normal conditions.

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment,

short-term (acute)

: Not available

Hazardous to the aquatic environment, :

ong-term (chronic)

: Not available

long-term (chronic)

Lubricant base oil		
LC50 - Other aquatic organisms [1]	> 1000 mg/l	
EC50 - Crustacea [1]	> 1000 mg/l	
Phosphorodithioic acid, mixed 0,0-bis(sec-Bu and isooctyl) esters, zinc salts (113706-15-3)		
LC50 - Fish [1]	= 4,5 mg/l	
EC50 - Crustacea [1]	= 5,4 mg/l	
Ethylenediamine (107-15-3)		
LC50 - Fish [1]	= 640 mg/l	
EC50 - Crustacea [1]	= 16,7 mg/l	
NOEC chronic fish	> 10 mg/l	
NOEC chronic crustacea	> 0,16 mg/l	

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available



Product: LUBRAX TRM 50

SDS ID: 1016653 Revision date: 03/02/2023

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

Regional legislation (waste) : Law No. 12.305 on the National Policy on Solid Waste Management, 02

August 2010.

Waste treatment methods : Must follow special treatment according to local regulation.

Sewage disposal recommendations : Disposal must be done according to official regulations.

Product/Packaging disposal : Disposal must be done according to official regulations. recommendations

Additional information : Do not re-use empty containers.

SECTION 14: Transport information

14.1 National and international Regulations

Not classified as dangerous for transport in the different modes, but may be harmful in the event of an accident. For further information, please consult Section 2 in this MSDS.

14.2 Other information

No additional information available

SECTION 15: Regulatory information

15.1. National regulations

Brazil Local Regulations : Norma ABNT NBR 14725.

Decreto Federal nº 2.657, de 3 de julho de 1998 - Promulga a Convenção nº 170 da OIT, relativa à Segurança na Utilização de Produtos Químicos no Trabalho, assinada em Genebra, em 25 de junho

de 1990.

Portaria nº 229, de 24 de maio de 2011 - Altera a Norma

Regulamentadora nº 27

Federal Decree no. 96.044, of 18 May 1988 - Approves Regulations for

Road Transportation of Hazardous Materials

Resolution no. 5947, of 01 June 2021, updates the regulation for road

transport of dangerous goods and approves its complementary

instructions, and other measures.

SECTION 16: Other information

No additional information available



Product: LUBRAX TRM 50

SDS ID: 1016653 Revision date: 03/02/2023

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.